

FLOOD RISK ASSESSMENT AND DRAINAGE STRATEGY

Proposed Residential
Development

Land off 52 New Street
Ash
Wingham
Kent
CT3 2BN

Prepared for:
Classicus Estates Limited

8th November 2022

Project Number:
RMA-C2432



environmental planning consultancy

THIS PAGE HAS BEEN LEFT BLANK INTENTIONALLY

Document Production Record:

Report Number: RMA-RC2432

Prepared by: Rosie Tutton

Checked by: Nick Yeo

Approved by: Rob Murdock

Document Revision Record:

Issue Number	Date	Revision Details
1	22 nd September 2022	Client Issue
2	29 th September 2022	Revised Client Issue
3	18 th October 2022	Final
4	8 th November 2022	Revised Final

RMA Environmental Limited has prepared this report in accordance with the instructions of the above named client for their sole and specific use. Any third parties who may use the information contained herein do so at their own risk.

CONTENTS

1	INTRODUCTION	1
	Background	1
	Site Location And Land Use.....	1
	Proposed Development.....	1
	Requirements For A Flood Risk Assessment	1
2	BASELINE ENVIRONMENTAL CONDITIONS.....	3
	Topography	3
	Hydrology	3
	Geology And Hydrogeology	3
3	EXTERNAL FLOOD RISK.....	5
	Flooding Mechanisms	5
	Historic Flooding.....	5
	Surface Water Flooding	5
	Safe Access/Egress	6
	Land Use Vulnerability	6
	Other Considerations	6
4	DRAINAGE ASSESSMENT	7
	Introduction.....	7
	Discharge Method	7
	Existing Runoff Arrangements	7
	Proposed Runoff Rates.....	7
	Storage Estimate.....	8
	Suds Selection	8
	Proposed Drainage Strategy.....	10
	Water Quality Requirement.....	10
	Designing For Exceedance Events.....	10
	Long Term Maintenance Of SuDS.....	11
	Foul Drainage.....	11
5	CONCLUSIONS	12

FIGURES

Figure 1.1:	Site Location Plan
Figure 3.1:	EA's Flood Map for Planning
Figure 3.2:	EA's Surface Water Flood Map
Figure 3.3:	EA's Low Surface Flood Depth Map
Figure 4.1:	Outline Drainage Plan
Figure 4.2:	Exceedance Plan

APPENDICES

Appendix A:	Proposed Development Layout
Appendix B:	Topographical Survey

Appendix C:	Greenfield Runoff Rates
Appendix D:	Micro Drainage Estimates
Appendix E:	SuDS Maintenance Schedule
Appendix F:	Southern Water Map

1 INTRODUCTION

Background

- 1.1 RMA Environmental Limited was commissioned by ENTRAN on behalf of Classicus Estates Limited to prepare a Flood Risk Assessment (FRA) and drainage strategy to support an outline planning application for a proposed residential development on land off 52 New Street in Ash, near Wingham, Kent, CT3 2BN.
- 1.2 This FRA has been prepared in accordance with the National Planning Policy Framework (NPPF), associated Planning Practice Guidance (PPG) and Environment Agency (EA) standing advice on flood risk for new development.

Site Location and Land Use

- 1.3 The site is brownfield comprising an existing house, redundant offices, outbuildings, an area of hardstanding and open land. It extends to an area of 1.54 hectares (ha) and is located at National Grid Reference TR 29435 58325 (refer to Figure 1.1).
- 1.4 The site is bordered by the following land uses:
 - Sandwich Road is located to the north, beyond which lies agricultural land;
 - residential housing and industrial uses are located to the east and west;
 - New Street is located to the south; and
 - Cherry Garden Lane is located further to the west.
- 1.5 Access to the site is currently via New Street to the south of the site. Further details on site topography, geology and hydrology are set out in Section 2.

Proposed Development

- 1.6 This application seeks outline planning permission with all matters reserved (except for access) for the demolition of existing buildings, including 51-53 Sandwich Road, and the erection of up to 52 new homes, including affordable, access from New Street and Sandwich Road, together with associated parking, open space, landscaping, drainage and associated infrastructure (refer to Appendix A). This will include widening the existing access point off New Street, potential connection points to adjoining land and retaining a Victorian villa as a refurbished home.

Requirements for a Flood Risk Assessment

- 1.7 The requirements for FRAs are provided in the NPPF and associated PPG. Paragraph 167 of the NPPF (July 2021) requires that a site-specific FRA should be submitted with planning applications for:
 - all sites greater than 1 ha in Flood Zone 1;

- for sites of any size within Flood Zones 2 or 3;
- in an area within Flood Zone 1 which has critical drainage problems;
- in an area within Flood Zone 1 which is identified in a strategic flood risk assessment as being at increased flood risk in the future; and/or
- an area within Flood Zone 1 that may be subject to other sources of flooding, where its development would introduce a more vulnerable use.

1.8 The EA's Flood Zones are defined as follows:

- Flood Zone 1 is defined as land with little or no flood risk (an annual exceedance probability [AEP] of flooding of less than 0.1%);
- Flood Zone 2 is defined as having a medium flood risk (an AEP of between 0.1% and 0.5% for tidal areas or 0.1% and 1.0% for rivers); and
- Flood Zone 3 is defined as high risk (with an AEP of greater than 0.5% for tidal areas or greater than 1.0% for rivers).

1.9 The EA's Surface Water Flood Risk extents are defined as follows:

- Very low surface water flood risk is defined where *"each year, this area has a chance of flooding of less than 1 in 1000 (0.1%)."*
- Low surface water flood risk is defined where *"each year, the area has a chance of flooding of between 1 in 1000 (0.1%) and 1 in 100 (1%)."*
- Medium surface water flood risk is defined where *"each year, this area has a chance of flooding of between 1 in 100 (1%) and 1 in 30 (3.3%)."*
- High surface water flood risk is defined where *"each year, this area has a chance of flooding of greater than 1 in 30 (3.3%)."*

1.10 FRAs should describe and assess all flood risks (from rivers, the sea, surface water, sewers, reservoirs and groundwater) to and from the development and demonstrate how they will be managed, including an evaluation of climate change effects.

2 BASELINE ENVIRONMENTAL CONDITIONS

Topography

- 2.1 The site slopes downwards in a north-easterly direction (refer to Appendix B). The highest level is approximately 27.68 metres Above Ordnance Datum (mAOD) in the southern part of the site, falling to approximately 18.80 mAOD in the north-eastern corner of the site.

Hydrology

- 2.2 There are no 'main rivers'¹ within a 500 m radius of the site; the closest 'ordinary watercourse'² is an unnamed watercourse located along the majority of the northern boundary. However, this shallow ditch does not appear to have connectivity to the wider drainage network.
- 2.3 An unnamed watercourse, hereafter referred to as Sandwich Brook, is located approximately 50 m to the north-west of the site and flows in a north-easterly direction into Goshall Stream approximately 450 m to the north-east of the site. According to the Flood Estimation Handbook (FEH) web service, the Sandwich Brook has a small catchment of less than 0.5 km² at the nearest location to the site.
- 2.4 Goshall Stream is located approximately 290 m to the east of the site and flows in a northerly direction into the River Stour, a 'main river', approximately 2.6 km to the north-east of the site. The Goshall Stream flows into the River Stour (Kent) Internal Drainage Board (IDB) Administration Area approximately 1.4 km to the north-east of the site and is classified by the EA as a 'main river' approximately 2 km to the north-east of the site. According to the FEH web service, the Goshall Stream has a small catchment of less than 0.5 km² at the nearest location to the site.
- 2.5 There are no other significant watercourses or water bodies within the surrounding area.

Geology and Hydrogeology

- 2.6 When reviewing the British Geological Survey (BGS) online map viewer, the majority of the site is underlain by the superficial geology of Head deposits comprising clay and silt. A few areas within the site are not underlain by any superficial geology.
- 2.7 The EA classify the Head deposits as Unproductive Strata; these are defined as "*rock layers or drift deposits with low permeability that have negligible significance for water supply or river base flow.*"
- 2.8 The majority of the site is underlain by the bedrock geology of the Thanet Formation comprising sand, silt and clay. The southern part of the site is underlain by the bedrock geology of the Lambeth Group comprising sand.

¹ Main river is defined by the EA as any watercourse that contributes significantly to the hydrology of a catchment.

² Ordinary watercourse is defined by the EA as any watercourse including every river, stream, ditch, drain, cut, dyke, sluice, sewer (other than a public sewer) and passage through which water flows and which does not form part of a main river.

-
- 2.9 The EA classify the Thanet Formation and Lambeth Group as Secondary A Aquifers; these are defined as *“permeable layers capable of supporting water supplies at a local rather than strategic scale, and in some cases forming an important source of base flow to rivers. These are generally aquifers formerly classified as minor aquifers.”*
- 2.10 The site is not located within a groundwater Source Protection Zone (SPZ).

3 EXTERNAL FLOOD RISK

Flooding Mechanisms

- 3.1 The EA's flood map for planning (refer to Figure 3.1) indicates that the entire site is located within Flood Zone 1 (low risk). Land located within Flood Zones 2 and 3 (medium and high risk) is located approximately 490 m to the south-west of the site and is 11.1 m lower in elevation when compared to the site; however, the site does not drain towards this area. The area of flood zone downslope of the site is located approximately 1.5 km to the north-east and is 15.6 m lower in elevation when compared to the site. Therefore, with consideration of the predicted impacts of climate change on the Flood Zone 2 and 3 extents, it is concluded that the site will remain in Flood Zone 1 for its operational lifetime (assumed to be 100 years).
- 3.2 The EA's surface water flood risk map identifies that the majority of the site has a very low surface water flood risk with areas with up to a medium surface water flood risk (refer to Figure 3.2).
- 3.3 The Dover District Council Strategic Flood Risk Assessment (SFRA; Herrington, 2019) states that *'pumping stations can result in a bottleneck within the sewer system and as a result, can increase the risk of flooding in the surrounding areas'*. However, there are no records of sewer flooding in the vicinity of the site and a pumped connection for surface water or foul is not included within the development; therefore, the risk of sewer flooding is deemed to be low.
- 3.4 A review of the SFRA (Herrington, 2019) and EA flood maps, has identified that there are no other significant sources of flooding at the site, i.e. from reservoirs or groundwater.

Historic Flooding

- 3.5 The SFRA (Herrington, 2019) has been reviewed to identify any specific records of flooding within or adjacent to the site. No records have been identified from this review.
- 3.6 The EA's historic flood map indicates that there are no historic flood records for the site or surrounding area.

Surface Water Flooding

- 3.7 The EA's risk of flooding from surface water mapping (refer to Figure 3.2) shows that the majority of the site has a very low surface water flood risk; however, a number of areas throughout the site have a low or medium risk of surface water flooding.
- 3.8 There is an area of isolated ponding with up to a medium surface water flood risk in the south-western corner of the site. The area of ponding is almost entirely located outside of the site boundary and all of the proposed built development is located outside of the flood extent and, therefore, no mitigation measures are required.

- 3.9 Two surface water flow pathways with up to a low risk of surface water flooding are located in the northern part of the site which flow towards Sandwich Road. The EA's surface water model does not include drain along the northern boundary and, therefore, this flood risk is likely to be overestimated. This surface water flood risk event is beyond the 1% AEP design event and, therefore, no mitigation is required. However, as a precautionary approach the finished floor levels of the proposed dwellings along the boundary of Sandwich Road could be raised 150 mm above existing ground levels (i.e. plots 40 to 47 on the indicative layout).

Safe Access/Egress

- 3.10 Access/egress to the site would be via Sandwich Road to the north and New Street to the south. The access/egress routes are located entirely within Flood Zone 1 (low risk), as is the surrounding area.
- 3.11 It is noted that Sandwich Road and New Street are at risk of surface water flooding; however, it is considered unlikely that this would preclude access/egress as the majority of the low surface water flood depths are less than 300 mm (refer to Figure 3.3). Nevertheless, should access/egress not be possible, then a safe refuge is afforded within the proposed dwellings. Whilst this is not an ideal mitigation measure, it would ensure that occupants of the site would be safe until floodwaters receded to a level that would allow safe external egress.
- 3.12 On this basis, it is concluded that future occupants of the development would be safe during the design flood event for the operational lifetime of the development.

Land Use Vulnerability

- 3.13 Table 2 of the PPG sets out a schedule of land uses based on their vulnerability or sensitivity to flooding. According to Annex 3 of the NPPF, residential development is classified as 'more vulnerable' to flooding. Referring to Table 3 of the PPG, all land uses are considered appropriate within Flood Zone 1.
- 3.14 Additionally, the Ash Parish Council Neighbourhood Development Plan 2018-2037 (Adopted in September 2021) identifies that the site is allocated for residential development (Policy ANP7a).
- 3.15 Therefore, on the basis of land use vulnerability, the development should be deemed appropriate in planning policy terms in its proposed location.

Other Considerations

Ordinary Watercourse Consent

- 3.16 The proposed access point along the northern boundary may be subject to an ordinary watercourse consent if it affects the ditch along the northern boundary identified on OS mapping; however, it is not shown on the topographical survey so the impact on the ditch is unclear at this stage. If ordinary watercourse consent is required, it is not considered to be a significant constraint to the development.

4 DRAINAGE ASSESSMENT

Introduction

- 4.1 This drainage strategy has been prepared in accordance with Defra's "*Non-statutory technical standards for sustainable drainage systems*" (March 2015) to ensure that the proposed development does not increase flood risk to the site or elsewhere and where practicable reduces flood risk over the lifetime of the development.
- 4.2 Peak rainfall intensity is expected to increase as a result of climate change and, as such, storage calculations have included a 45% increase in rainfall depths in accordance with the current climate change guidance.

Discharge Method

- 4.3 The feasibility of infiltration-based SuDS will be confirmed via infiltration testing which was not completed at this stage given that the planning application is for outline permission.
- 4.4 If the results of infiltration testing and site investigation prove favourable, the proposed drainage strategy will utilise infiltration techniques. Infiltration-based SuDS would be sized appropriately to accommodate the 1 in 100 year storm including 45% for climate change and allow a half-drain time of less than 24 hours.
- 4.5 As infiltration techniques have not been confirmed to be feasible at this stage, an attenuation-based strategy has been provided for the 1 in 100 year storm including a 45% allowance for climate change. As such, it is proposed to discharge into Sandwich Brook to the north-west. A discharge to this watercourse could be achieved via a connection into a surface water sewer along Sandwich Road (via manhole 3454). This is considered to be acceptable as this sewer discharges into Sandwich Brook 10 m downstream.

Existing Runoff Arrangements

- 4.6 The existing site is brownfield comprising an existing house, redundant offices, outbuildings and an area of hardstanding; no details are available on the existing drainage arrangement, however, given the presence of buildings on the site, the existing runoff rates are significantly greater than greenfield runoff rates.

Proposed Runoff Rates

- 4.7 Greenfield runoff rates for the site have been estimated using the UK Sustainable Drainage Greenfield Runoff Estimation Tool. The calculation record is included in Appendix C and the results are summarised as follows:
- Qbar – 1.73 l/s/ha
 - 1 in 1 year – 1.47 l/s/ha
 - 1 in 30 years – 3.98 l/s/ha
 - 1 in 100 years – 5.53 l/s/ha

4.8 The proposed development will introduce impermeable areas which have been estimated as 8,360 m² (0.84 ha). The equivalent greenfield runoff rates for the proposed impermeable area are summarised as follows:

- Qbar – 1.45 l/s
- 1 in 1 year – 1.23 l/s
- 1 in 30 years – 3.34 l/s
- 1 in 100 years – 4.65 l/s

4.9 It is proposed to limit the rate of discharge for all events up to the 100 year plus 45% to 5.4 l/s. This discharge rate is proposed as this is the lowest rate to which runoff can be restricted without the half drain time exceeding 24 hours. Whilst this is greater than the greenfield equivalent, it will still result in a significant reduction in existing runoff rates, given the existing brownfield nature of the site.

Storage Estimate

4.10 The impermeable area of the proposed development is increased by 10% to account for urban creep over the lifetime of the development and an impermeable area of 9,196 m² (0.92 ha) has therefore been used to estimate the attenuation volume required.

4.11 A storage estimate has been undertaken using Micro Drainage to inform the outline drainage strategy; the results are included in Appendix D. This estimates that an attenuation volume of 893.3 m³ is required in order to limit the runoff rate to 5.4 l/s for all events up to and including the 1 in 100 year storm plus 45%.

SuDS Selection

4.12 Table 4.1 provides an overview of the feasibility of a range of SuDS techniques which are considered in accordance with the SuDS Hierarchy in order to identify the most appropriate for the proposed development. Further details are provided for the techniques which are considered to be feasible.

Table 4.1: Type of SuDS Components

Technique	Description	Suitability for Proposals	Feasibility
Green Roofs	A planted soil layer is constructed on the roof of a building and water is stored within the soil layer and absorbed by vegetation.	Limited value for runoff attenuation for extreme return periods and is not considered to be commercially viable for this residential development.	Not Feasible
Infiltration Systems	These systems collect and store runoff allowing it to infiltrate into the ground.	Infiltration techniques are potentially feasible, however, this would be determined through infiltration testing at a later stage.	Potentially Feasible
Filter Strips	Runoff from an impermeable area is allowed to flow across a grassed or heavily vegetated area to promote sedimentation and filtration.	Could be used within open space to provide treatment and would be considered at the detailed design stage.	Potentially Feasible

Technique	Description	Suitability for Proposals	Feasibility
Filter Drains	Runoff is temporarily stored below the surface in a shallow trench filled with clean stone, providing attenuation, conveyance and filtration.	Normally used for the drainage of hardstanding areas. They could be used to collect and treat runoff and would be considered at the detailed design stage.	Potentially Feasible
Swales	A vegetated channel is used to convey and treat runoff (via filtration). It can be used as attenuation space with discharge to the ground (via infiltration) or to a watercourse or sewer.	Swales are not considered to be feasible for the site due to the limited area of open space within the proposed development.	Not Feasible
Bioretention Systems (Rain Gardens)	A shallow landscaped depression allows runoff to pond temporarily on the surface before filtering through vegetation and underlying soils prior to collection or infiltration.	Could be used within open space to provide treatment.	Potentially Feasible
Permeable Pavements	Runoff is allowed to soak through structural paving. Water can be stored in a porous sub-base and either collected or allowed to infiltrate.	Permeable paving could be used beneath the car parking areas and roads.	Feasible
Attenuation Basins	Landscaped depressions that are normally dry except during and following rainfall, designed to attenuate runoff and, where vegetated, provide treatment.	Attenuation basins are considered to be feasible to provide attenuation storage.	Feasible
Ponds and Wetlands	Depressions designed to temporarily store surface water above permanently wet pools that permit settlement of suspended solids and biological removal of pollutants.	Could be used to attenuate runoff as an alternative to a basin and would be considered at the detailed design stage.	Potentially Feasible
Geo-cellular Storage	Structures that create a below-ground void space for the temporary storage of surface water before controlled release or use (rainwater harvesting).	Could be used to attenuate runoff under areas of hardstanding such as car parking areas and roads.	Feasible

Proposed Drainage Strategy

- 4.13 Areas of green space have been incorporated into the illustrative layout to allow the inclusion of above ground SuDS. This could include an attenuation basin, bio-retention areas, rain gardens and tree pits which will provide source control features, water quality treatment, encourage evaporation and transpiration. The depth of the basin could be up to 1 m which would be confirmed in the detailed design. Wherever practicable, runoff will first be directed to these features before draining into the geo-cellular storage. As a conservative approach, the storage volume provided by the above ground SuDS has not been included in the storage estimates below.
- 4.14 It is also proposed to include permeable paving to provide water quality treatment prior to runoff entering the geo-cellular storage.
- 4.15 Whilst above ground SuDS have been utilised, it is necessary to also include below ground storage to achieve the volume of attenuation needed, as a result of space constraints.
- 4.16 The attenuation volume of 893.3 m³ could be provided in the form of geo-cellular storage throughout the site (refer to Figure 4.1). The geo-cellular storage shown has a plan area of 945 m², a depth of 1 m and a void space of 95%. The geo-cellular storage could be overlain with a granular sub-base or permeable paving to provide water quality treatment.

Water Quality Requirement

- 4.17 One of the guiding principles of SuDS is the appropriate management of water quality and the use of pollution prevention techniques to improve the quality of runoff from developed sites. The SuDS Manual recommends the use of a management train whereby a series of consecutive treatment stages are employed to remove pollutants from runoff.
- 4.18 The recommended number of treatment stages is dependent on the type of development and sensitivity of the discharge receptor and the mitigation indices of proposed SuDS features. Surface water requiring treatment will come from the roofs, access road, driveways and parking areas. In this instance, mitigation with an index or combined indices of more than 0.5 for Total Suspended Solids (TSS), 0.4 for metals and 0.4 for hydrocarbons is acceptable.
- 4.19 The basin, bio-retention areas, tree pits and rain gardens, as well as the granular sub-base and permeable/grass paving system overlying the geo-cellular storage will meet the water quality requirements required for the proposed development. The granular material will provide a similar to the level of treatment provided by permeable paving.

Designing for Exceedance Events

- 4.20 If the proposed drainage system was to become blocked or an event above the design event occur, it is considered likely that some additional storage would be provided in the form of shallow flooding of hard-paved areas. Any water leaving the site would be routed along the road network towards the northern boundary and into Sandwich Brook (refer to Figure 4.2). This would mimic what would occur naturally on the site in its existing condition and would ensure that the proposed dwellings are safe during an exceedance event.

Long Term Maintenance of SuDS

- 4.21 Where SuDS features serve more than one property, it would be the responsibility of the developer to either maintain the SuDS features themselves or to negotiate with and secure the agreement of a third party to maintain the sustainable drainage system.
- 4.22 The maintenance requirements of the proposed SuDS features for use in the outline drainage strategy are detailed in the SuDS Manual and would be carried out accordingly (refer to Appendix E).

Foul Drainage

- 4.23 Southern Water mapping extracted from the Essential Utility Search Report indicates that a 100 mm foul rising main is located approximately 6 m to the north along Sandwich Road and the 150 mm public foul sewer is located approximately 12 m to the north-west of the site (refer to Appendix F).
- 4.24 Therefore, a connection into the foul sewer along Sandwich Road is considered to be feasible subject to consultation with Southern Water to establish if there is sufficient capacity in the local network. The proposed development will not be occupied until any potential off-site upgrades by Southern Water are completed, which will be secured under the Section 106 of the Water Industry Act.

5 CONCLUSIONS

- 5.1 The requirements for Flood Risk Assessment are provided in the National Planning Policy Framework and its associated Planning Practice Guidance, together with the Environment Agency's Guidance Notes. This policy and associated guidance have been followed in the preparation of this FRA.
- 5.2 The EA's flood map for planning indicates that the entire site is located within Flood Zone 1 (low risk). Land located within Flood Zones 2 and 3 (medium and high risk) is located approximately 490 m to the south-west of the site and is 11.1 m lower in elevation when compared to the site; however, the site does not drain towards this area of flood zone. The area of flood zone downslope of the site is located approximately 1.5 km to the north-east and is 15.6 m lower in elevation when compared to the site. Therefore, with consideration of the predicted impacts of climate change on the Flood Zone 2 and 3 extents, it is concluded that the site will remain in Flood Zone 1 for its operational lifetime.
- 5.3 The EA's surface water flood risk map identifies that the majority of the site has a very low surface water flood risk with areas with up to a medium surface water flood risk. There is an area of isolated ponding with up to a medium surface water flood risk in the south-west corner of the site. The area of ponding is almost entirely located outside of the site boundary and all of the proposed built development is located outside of the flood extent and, therefore, no mitigation measures are required.
- 5.4 Two surface water flow pathways with up to a low risk of surface water flooding are located in the northern part of the site which flow towards Sandwich Road. The EA's surface water model does not include drain along the northern boundary and, therefore, this flood risk is likely to be overestimated. This surface water flood risk event is beyond the 1% AEP design event and, therefore, no mitigation is required. However, as a precautionary approach the finished floor levels of the proposed dwellings along the boundary of Sandwich Road could be raised 150 mm above existing ground levels (i.e. plots 40 to 47 on the indicative layout).
- 5.5 The Dover District Council SFRA states that '*pumping stations can result in a bottleneck within the sewer system and as a result, can increase the risk of flooding in the surrounding areas*'. However, there are no records of sewer flooding in the vicinity of the site and a pumped connection for surface water or foul is not included within the site; therefore, the risk of sewer flooding is deemed to be low.
- 5.6 Access/egress to the site would be via Sandwich Road and New Street. The access/egress routes are located entirely within Flood Zone 1, as is the surrounding area. It is noted that these routes are at risk of surface water flooding; however, it is considered unlikely that this would preclude access/egress as the majority of the low surface water flood depths are less than 300 mm. Nevertheless, should access/egress not be possible, then a safe refuge is afforded within the proposed dwellings. Whilst this is not an ideal mitigation measure, it would ensure that occupants of the site would be safe until floodwaters receded to a level that would allow safe external egress.

-
- 5.7 The feasibility of infiltration-based SuDS will be confirmed via infiltration testing which was not completed at this stage of the development given that the planning application is for outline permission.


 - 5.8 As infiltration techniques have not been confirmed to be feasible at this stage, an attenuation-based strategy has been provided. As such, it is proposed to discharge into Sandwich Brook via a connection into a surface water sewer along Sandwich Road. This is considered to be acceptable as this sewer discharges into Sandwich Brook 10 m downstream.

 - 5.9 Areas of green space have been incorporated into the illustrative layout to demonstrate the inclusion of above ground SuDS. This will include an attenuation basin, bio-retention areas, rain gardens and tree pits which will provide source control features, water quality treatment, encourage evaporation and transpiration. Wherever practicable, runoff will first be directed to these features before draining into the geo-cellular storage.

 - 5.10 The proposed drainage strategy utilises geo-cellular storage to ensure that surface water runoff rates for the proposed development are limited to the 5.4 l/s for all events up to and including the 1 in 100 year plus 45% CC event.

 - 5.11 This FRA has therefore demonstrated that the proposed development will be safe and that it would not increase flood risk elsewhere. The residential development is classified as 'more vulnerable' to flooding. This land use is considered appropriate in relation to the flood risk vulnerability classifications set out in Table 3 of the PPG. The development should therefore be considered acceptable in planning policy terms.

Figures



Key
 Application Site


Figure 1.1: **Site Location Plan**

Client: **Classicus Estates Limited**

Project: **Ash Sandwich**

Project No.: **C2438**

Drawn: RT	Checked: NY	Date: 08/11/2022	Scale: 1:5,000@A3
--------------	----------------	---------------------	----------------------



Key

- Application Site
- Flood Zone 2
- Flood Zone 3

Figure 3.1: **EA's Flood Map for Planning**

Client: **Classicus Estates Limited**

Project: **Ash Sandwich**

Project No.: **C2438**



Drawn: RT	Checked: NY	Date: 08/11/2022	Scale: 1:5,000@A3
--------------	----------------	---------------------	----------------------



Key


- Application Site
- Low Risk
- Medium Risk
- High Risk

Figure 3.2: **EA's Surface Water Flood Map**

Client:	Classicus Estates Limited
Project:	Ash Sandwich
Project No.:	C2438



Drawn: RT	Checked: NY	Date: 08/11/2022	Scale: 1:1,000@A3
--------------	----------------	---------------------	----------------------



Key

Application Site

Flood Depths

- Below 150 mm
- 150 mm - 300 mm
- 300 mm - 600 mm
- 600 mm - 900 mm
- 900 mm - 1200 mm
- Over 1200 mm

Figure 3.3: EA's Low Surface Water Flood Depth Map

Client:	Classicus Estates Limited
Project:	Ash Sandwich
Project No.:	C2438



Drawn: RT	Checked: NY	Date: 08/11/2022	Scale: 1:1,500@A3
--------------	----------------	---------------------	----------------------



Key

- Application Site
- Geo-cellular Storage
- Basin
- Indicative Discharge
- Bio-retention Area/ Rain Garden/ Tree Pits
- Permeable Paving

Figure 4.1: Outline Drainage Plan

Client: **Classicus Estates Limited**

Project: **Ash Sandwich**

Project No.: **C2432**



Drawn:
RT

Checked:
NY

Date:
08/11/2022

Scale:
1:750@A3




Ordnance Survey © Crown Copyright 2015. All rights reserved. Licence number 100022432. Contains public sector information licensed under the Open Government Licence v3.0.

Key Application Site Exceedance Route		Figure 4.2: Exceedance Plan			
		Client:	Classicus Estates Limited		
		Project:	Ash Sandwich		
		Project No.:	C2432	Drawn: RT	Checked: NY
				Date: 08/11/2022	Scale: 1:750@A3

Appendix A: Proposed Development Layout

Proposed Site Plan
1:500



Indicative Schedule of Accommodation

Unit No.	Size	Type
1	-	Existing Dwelling
2	93	3Bed 5Person House
3	93	3Bed 5Person House
4	115	4Bed 7Person House
5	93	3Bed 5Person House
6	93	3Bed 5Person House
7	93	3Bed 5Person House
8	93	3Bed 5Person House
9	79	2Bed 4Person House
10	115	4Bed 7Person House
11	121	4Bed 7Person House (2.5)
12	121	4Bed 7Person House (2.5)
13	121	4Bed 7Person House (2.5)
14	121	4Bed 7Person House (2.5)
15	115	4Bed 7Person House
16	115	4Bed 7Person House
17	93	3Bed 5Person House
18	93	3Bed 5Person House
19	93	3Bed 5Person House
20	93	3Bed 5Person House
21	93	3Bed 5Person House
22	99	3Bed 5Person House (2.5)
23	99	3Bed 5Person House (2.5)
24	99	3Bed 5Person House (2.5)
25	99	3Bed 5Person House (2.5)
26	50	1Bed 2Person Flat G.F. - Affordable
27	70	2Bed 4Person Flat F.F. - Affordable
28	70	2Bed 4Person Flat F.F. - Affordable
29	70	2Bed 4Person Flat F.F. - Affordable
30	70	2Bed 4Person Flat F.F. - Affordable
31	70	2Bed 4Person Flat F.F. - Affordable
32	70	2Bed 4Person Flat (F.O.G.) - Affordable
33	121	4Bed 7Person House (2.5)
34	121	4Bed 7Person House (2.5)
35	121	4Bed 7Person House (2.5)
36	121	4Bed 7Person House (2.5)
37	115	4Bed 7Person House
38	70	2Bed 4Person Flat (F.O.G.)
39	70	2Bed 4Person Flat (F.O.G.)
40	79	2Bed 4Person House
41	79	2Bed 4Person House
42	79	2Bed 4Person House
43	79	2Bed 4Person House
44	79	2Bed 4Person House
45	79	2Bed 4Person House
46	70	2Bed 4Person Flat G.F. - Affordable
47	70	2Bed 4Person Flat F.F. - Affordable
48	70	2Bed 4Person Flat G.F. - Affordable
49	70	2Bed 4Person Flat F.F. - Affordable
50	61	2Bed 3Person Flat (F.O.G.) - Affordable
51	79	2Bed 4Person House - Affordable
52	79	2Bed 4Person House - Affordable
53	79	2Bed 4Person House - Affordable

Total = 4703 sqm gfa (50,624 sqft gfa)

Summary : 1no. 1Bed Flat
13no. 2Bed Flats
10no. 2Bed Houses
15no. 3Bed Houses
13no. 4Bed Houses

52no. New Homes + Existing Dwelling (Plot1) = 53 Total

Suggested Affordable - 15no. dwellings - Plots 26-32 and 46-53
(1 x 1 bed and 14 x 2 beds)

54 - 61 : Adjacent Site - Illustrative Layout for 8no. Dwellings
62 - 76 : Outline Planning Submission by ON Architecture (20/00284)
77 - 100 : Detailed Planning Submission by ON Architecture (20/00284)

A	Junctions Updated	RT	NDT	25.10.22
-	Original Issue	RT	NDT	20.10.22
REV.		BY	CH'K'D	DATE




PROJECT: 52 New Street, Ash,
Nr. Canterbury, Kent.

CLIENT: Classicus Estates Ltd.

DRAWING: Proposed Site Plan Colour,
Showing All Land Parcels,
Option 1.

SCALE(SHEET SIZE): JOB NO.: REV.:
1:500 (A1) 22/23/05 A

Appendix B: Topographical Survey



LEGEND

AV	AIR VALVE
B	BOLLARD
BL	BASE LEVEL
CATV	CABLE TV INSPECTION COVER
CL	COVER LEVEL
DP	DOWN PIPE
EIC	ELECTRICAL INSPECTION COVER
EP	ELECTRICITY POLE
FH	FIRE HYDRANT
FL	FLOOR LEVEL
G	GULLY
GIC	GAS SERVICE INSPECTION COVER
IC	INSPECTION COVER
IL	INVERT LEVEL
JB	JUNCTION BOX
LC	LIGHTING COLUMN
LM	MANHOLE COVER
MS	(S) STORM, (F) FOUL, (C) COMBINED SERVICES MARKER
PK	POST
RE	RODDING EYE
RNP	ROAD NAME PLATE
RS	ROAD SIGN
RWP	RAINWATER PIPE
SC(G)	STOP COCK (GAS)
SC(W)	STOP COCK (WATER)
STN	SURVEY CONTROL STATION WITH LEVEL
SU	STEP UP
SV	STOP VALVE
SVP	SOIL VENT PIPE
THL	THRESHOLD LEVEL
TIC	TELECOM INSPECTION COVER
TOW	TOP OF WALL
TP	TELECOM POLE
WIC	WATER SERVICE INSPECTION COVER
WM	WATER METER
WO	WASH OUT

TREE DESCRIPTION		
SYCAMORE		=SPECIES
H=12m		= TREE HEIGHT
2 boles		= EXTRA INFORMATION

NOTES

1. ALL LEVELS RELATED TO ORDNANCE SURVEY DATUM DERIVED FROM GPS OBSERVATIONS.

2. SURVEY SPREADSHEET DATA TO ORDNANCE SURVEY DATUM DERIVED FROM GPS OBSERVATIONS WITH A SCALE FACTOR OF 1.

3. NO RESPONSIBILITY CAN BE TAKEN FOR THE INCORRECT IDENTIFICATION OF TREE, HEDGE OR VEGETATION SPECIES.

4. TREE BOLE AND CANOPY SPREADS HAVE BEEN SHOWN TO SCALE AND WHERE POSSIBLE THE EXTENT OF TREE CANOPIES HAVE BEEN SURVEYED.

SURVEY STATIONS				
Name	Eastings	Northings	Height	Remark
1	629408.141	158392.770	26.261	Survey Nail
2	629410.843	158248.871	27.285	Survey Nail
3	629404.443	158234.855	27.551	Survey Nail
4	629401.732	158228.153	27.654	Survey Nail
5	629396.879	158218.287	27.636	Survey Nail
6	629414.235	158231.378	27.483	Survey Nail
6	629408.433	158205.325	27.404	Survey Nail
7	629376.230	158221.205	28.379	Survey Nail

Reproduced from Ordnance Survey digital map data © Crown copyright August 2022. All rights reserved. Licence number 100001615

ORDNANCE SURVEY DIGITAL DATA SHOWN IN GREY

ANISURVEYS Ltd
3 Sleigh Road, Barry, Kent, CT3 2BN
Tel: 01227 710316
email: anis@anisurveys.co.uk
www.anisurveys.co.uk


Drawing Title

TOPOGRAPHICAL SURVEY OF LAND AT
52 NEW STREET ASH, KENT, CT3 2BN

Client

CLASSICUS ESTATES

Drawing Number	3
Original Sheet Size and Scale	A0 AT 1:200
Drawn By	A. NICHOLSON
Date	01st August 2022
Ad Filename	NEW STREET ASH FINAL.dwg
Revision	



LEGEND

AV	AIR VALVE
B	BOLLARD
BL	BASE LEVEL
CATV	CABLE TV INSPECTION COVER
CL	COVER LEVEL
DP	DOWN PIPE
EIC	ELECTRICAL INSPECTION COVER
EP	ELECTRICITY POLE
FH	FIRE HYDRANT
FL	FLOOR LEVEL
G	GULLY
GIC	GAS SERVICE INSPECTION COVER
IC	INSPECTION COVER
IL	INVERT LEVEL
JB	JUNCTION BOX
LC	LIGHTING COLUMN
LM	MANHOLE COVER
MS	(S) STORM, (F) FOUL, (C) COMBINED
MK	SERVICES MARKER
P	POST
RE	RODDING EYE
RNP	ROAD NAME PLATE
RS	ROAD SIGN
RWP	RAINWATER PIPE
SC(G)	STOP COCK (GAS)
SC(W)	STOP COCK (WATER)
STN	SURVEY CONTROL STATION WITH LEVEL
SU	STEP UP
SV	STOP VALVE
SVP	SOIL VENT PIPE
THL	THRESHOLD LEVEL
TIC	TELECOM INSPECTION COVER
TOW	TOP OF WALL
TP	TELECOM POLE
WIC	WATER SERVICE INSPECTION COVER
WM	WATER METER
WO	WASH OUT

TREE DESCRIPTION	
SYCAMORE	=SPECIES
H=12m	= TREE HEIGHT
Z=boles	= EXTRA INFORMATION

NOTES
1. ALL LEVELS RELATED TO ORDNANCE SURVEY DATUM DERIVED FROM GPS OBSERVATIONS.
2. SURVEY SPREADSHEET TO ORDNANCE SURVEY DATUM DERIVED FROM GPS OBSERVATIONS WITH A SCALE FACTOR OF 1.
3. NO RESPONSIBILITY CAN BE TAKEN FOR THE INCORRECT IDENTIFICATION OF TREE, HEDGE OR VEGETATION SPECIES.
4. TREE BOLE AND CANOPY SPREADS HAVE BEEN SHOWN TO SCALE AND WHERE POSSIBLE THE EXTENT OF TREE CANOPIES HAVE BEEN SURVEYED.

SURVEY STATIONS				
Name	Eastings	Northings	Height	Remark
1	629408.141	158292.170	26.261	Survey Nail
2	629410.843	158248.871	27.285	Survey Nail
3	629404.443	158234.855	27.551	Survey Nail
4	629401.732	158228.153	27.654	Survey Nail
5	629396.879	158218.287	27.636	Survey Nail
6	629414.235	158231.378	27.483	Survey Nail
7	629408.431	158205.325	27.404	Survey Nail
8	629376.230	158221.205	28.379	Survey Nail

Reproduced from Ordnance Survey digital map data © Crown copyright August 2002. All rights reserved. Licence number 100001675
ORDNANCE SURVEY DIGITAL DATA SHOWN IN GREY

ANISURVEYS Ltd
3 Sleigh Road, Surry, Kent, CT3 2HR
Tel: 01227 710316
email: anis@anisurveys.co.uk
www.anisurveys.co.uk

Drawing Title
TOPOGRAPHICAL SURVEY OF LAND AT
52 NEW STREET ASH, KENT, CT3 2BN

Client
CLASSICUS ESTATES

Drawing Number
1

Original Sheet Size and Scale
A0 AT 1:200

Drawn By
A. NICHOLSON

Date
08th August 2022

Cad Filename
NEW STREET ASH FINAL.dwg

Revision

Appendix C: Greenfield Runoff Rates

[Print](#)[Close Report](#)

Greenfield runoff rate estimation for sites

www.uksuds.com | Greenfield runoff tool

Calculated by: Rosie Tutton

Site name: Ash

Site location: Sandwich

Site Details

Latitude: 51.27761° N

Longitude: 1.28828° E

Reference: 3623128991

Date: Sep 19 2022 19:27

This is an estimation of the greenfield runoff rates that are used to meet normal best practice criteria in line with Environment Agency guidance "Rainfall runoff management for developments", SC030219 (2013), the SuDS Manual C753 (Ciria, 2015) and the non-statutory standards for SuDS (Defra, 2015). This information on greenfield runoff rates may be the basis for setting consents for the drainage of surface water runoff from sites.

Runoff estimation approach: FEH Statistical

Site characteristics

Total site area (ha): 1

Methodology

Q_{MED} estimation method: Calculate from BFI and SAAR

BFI and SPR method: Specify BFI manually

HOST class: N/A

BFI / BFIHOST: 0.615

Q_{MED} (l/s):

Q_{BAR} / Q_{MED} factor: 1.14

Hydrological characteristics

	Default	Edited
SAAR (mm):	638	638
Hydrological region:	7	7
Growth curve factor 1 year:	0.85	0.85
Growth curve factor 30 years:	2.3	2.3
Growth curve factor 100 years:	3.19	3.19
Growth curve factor 200 years:	3.74	3.74

Notes

(1) Is $Q_{BAR} < 2.0$ l/s/ha?

When Q_{BAR} is < 2.0 l/s/ha then limiting discharge rates are set at 2.0 l/s/ha.

(2) Are flow rates < 5.0 l/s?

Where flow rates are less than 5.0 l/s consent for discharge is usually set at 5.0 l/s if blockage from vegetation and other materials is possible. Lower consent flow rates may be set where the blockage risk is addressed by using appropriate drainage elements.

(3) Is $SPR/SPRHOST \leq 0.3$?


Where groundwater levels are low enough the use of soakaways to avoid discharge offsite would normally be preferred for disposal of surface water runoff.


Greenfield runoff rates

	Default	Edited
Q_{BAR} (l/s):		1.73
1 in 1 year (l/s):		1.47
1 in 30 years (l/s):		3.98
1 in 100 year (l/s):		5.53
1 in 200 years (l/s):		6.48

This report was produced using the greenfield runoff tool developed by HR Wallingford and available at www.uksuds.com. The use of this tool is subject to the UK SuDS terms and conditions and licence agreement, which can both be found at www.uksuds.com/terms-and-conditions.htm. The outputs from this tool are estimates of greenfield runoff rates. The use of these results is the responsibility of the users of this tool. No liability will be accepted by HR Wallingford, the Environment Agency, CEH, Hydrosolutions or any other organisation for the use of this data in the design or operational characteristics of any drainage scheme.

Appendix D: Micro Drainage Estimates

RMA Environmental Ltd							Page 1																																																																																																																																																																																																																																																																																	
4 Swallow Court Devonshire Gate, Tiverton Devon, EX16 7EJ																																																																																																																																																																																																																																																																																								
Date 29/09/2022 16:15 File C2432 GEOCELL.SRCX			Designed by rosie.tutton Checked by																																																																																																																																																																																																																																																																																					
Innovyze			Source Control 2020.1																																																																																																																																																																																																																																																																																					
<p style="text-align: center;"><u>Summary of Results for 100 year Return Period (+45%)</u></p> <p style="text-align: center;">Half Drain Time : 1424 minutes.</p> <table><tr><th>Storm Event</th><th>Max Level (m)</th><th>Max Depth (m)</th><th>Max Infiltration (l/s)</th><th>Max Control (l/s)</th><th>Max Σ Outflow (l/s)</th><th>Max Volume (m³)</th><th>Status</th></tr><tr><td>15 min Summer</td><td>18.727</td><td>0.427</td><td>0.0</td><td>5.4</td><td>5.4</td><td>383.0</td><td>O K</td></tr><tr><td>30 min Summer</td><td>18.790</td><td>0.490</td><td>0.0</td><td>5.4</td><td>5.4</td><td>439.7</td><td>O K</td></tr><tr><td>60 min Summer</td><td>18.859</td><td>0.559</td><td>0.0</td><td>5.4</td><td>5.4</td><td>502.3</td><td>O K</td></tr><tr><td>120 min Summer</td><td>18.934</td><td>0.634</td><td>0.0</td><td>5.4</td><td>5.4</td><td>569.2</td><td>O K</td></tr><tr><td>180 min Summer</td><td>18.978</td><td>0.678</td><td>0.0</td><td>5.4</td><td>5.4</td><td>608.6</td><td>O K</td></tr><tr><td>240 min Summer</td><td>19.008</td><td>0.708</td><td>0.0</td><td>5.4</td><td>5.4</td><td>635.2</td><td>Flood Risk</td></tr><tr><td>360 min Summer</td><td>19.044</td><td>0.744</td><td>0.0</td><td>5.4</td><td>5.4</td><td>668.2</td><td>Flood Risk</td></tr><tr><td>480 min Summer</td><td>19.065</td><td>0.765</td><td>0.0</td><td>5.4</td><td>5.4</td><td>686.4</td><td>Flood Risk</td></tr><tr><td>600 min Summer</td><td>19.075</td><td>0.775</td><td>0.0</td><td>5.4</td><td>5.4</td><td>696.1</td><td>Flood Risk</td></tr><tr><td>720 min Summer</td><td>19.080</td><td>0.780</td><td>0.0</td><td>5.4</td><td>5.4</td><td>700.1</td><td>Flood Risk</td></tr><tr><td>960 min Summer</td><td>19.113</td><td>0.813</td><td>0.0</td><td>5.4</td><td>5.4</td><td>730.1</td><td>Flood Risk</td></tr><tr><td>1440 min Summer</td><td>19.145</td><td>0.845</td><td>0.0</td><td>5.4</td><td>5.4</td><td>758.3</td><td>Flood Risk</td></tr><tr><td>2160 min Summer</td><td>19.165</td><td>0.865</td><td>0.0</td><td>5.4</td><td>5.4</td><td>776.7</td><td>Flood Risk</td></tr><tr><td>2880 min Summer</td><td>19.170</td><td>0.870</td><td>0.0</td><td>5.4</td><td>5.4</td><td>781.4</td><td>Flood Risk</td></tr><tr><td>4320 min Summer</td><td>19.055</td><td>0.755</td><td>0.0</td><td>5.4</td><td>5.4</td><td>678.1</td><td>Flood Risk</td></tr><tr><td>5760 min Summer</td><td>18.951</td><td>0.651</td><td>0.0</td><td>5.4</td><td>5.4</td><td>584.0</td><td>O K</td></tr><tr><td>7200 min Summer</td><td>18.843</td><td>0.543</td><td>0.0</td><td>5.4</td><td>5.4</td><td>487.8</td><td>O K</td></tr><tr><td>8640 min Summer</td><td>18.758</td><td>0.458</td><td>0.0</td><td>5.4</td><td>5.4</td><td>410.8</td><td>O K</td></tr><tr><td>10080 min Summer</td><td>18.686</td><td>0.386</td><td>0.0</td><td>5.4</td><td>5.4</td><td>346.6</td><td>O K</td></tr><tr><td>15 min Winter</td><td>18.778</td><td>0.478</td><td>0.0</td><td>5.4</td><td>5.4</td><td>429.3</td><td>O K</td></tr></table> <table><tr><th>Storm Event</th><th>Rain (mm/hr)</th><th>Flooded Volume (m³)</th><th>Discharge Volume (m³)</th><th>Time-Peak (mins)</th></tr><tr><td>15 min Summer</td><td>224.312</td><td>0.0</td><td>351.6</td><td>19</td></tr><tr><td>30 min Summer</td><td>129.531</td><td>0.0</td><td>398.4</td><td>34</td></tr><tr><td>60 min Summer</td><td>74.799</td><td>0.0</td><td>502.0</td><td>64</td></tr><tr><td>120 min Summer</td><td>43.194</td><td>0.0</td><td>578.9</td><td>124</td></tr><tr><td>180 min Summer</td><td>31.327</td><td>0.0</td><td>628.2</td><td>184</td></tr><tr><td>240 min Summer</td><td>24.943</td><td>0.0</td><td>665.0</td><td>242</td></tr><tr><td>360 min Summer</td><td>18.090</td><td>0.0</td><td>718.4</td><td>362</td></tr><tr><td>480 min Summer</td><td>14.403</td><td>0.0</td><td>755.6</td><td>482</td></tr><tr><td>600 min Summer</td><td>12.070</td><td>0.0</td><td>781.4</td><td>602</td></tr><tr><td>720 min Summer</td><td>10.446</td><td>0.0</td><td>796.8</td><td>722</td></tr><tr><td>960 min Summer</td><td>8.644</td><td>0.0</td><td>800.4</td><td>960</td></tr><tr><td>1440 min Summer</td><td>6.620</td><td>0.0</td><td>764.7</td><td>1242</td></tr><tr><td>2160 min Summer</td><td>5.069</td><td>0.0</td><td>1244.5</td><td>1640</td></tr><tr><td>2880 min Summer</td><td>4.195</td><td>0.0</td><td>1365.8</td><td>2044</td></tr><tr><td>4320 min Summer</td><td>2.928</td><td>0.0</td><td>1385.8</td><td>2856</td></tr><tr><td>5760 min Summer</td><td>2.269</td><td>0.0</td><td>1499.1</td><td>3696</td></tr><tr><td>7200 min Summer</td><td>1.862</td><td>0.0</td><td>1537.1</td><td>4400</td></tr><tr><td>8640 min Summer</td><td>1.584</td><td>0.0</td><td>1567.6</td><td>5104</td></tr><tr><td>10080 min Summer</td><td>1.382</td><td>0.0</td><td>1590.9</td><td>5848</td></tr><tr><td>15 min Winter</td><td>224.312</td><td>0.0</td><td>388.8</td><td>19</td></tr></table>								Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max Σ Outflow (l/s)	Max Volume (m³)	Status	15 min Summer	18.727	0.427	0.0	5.4	5.4	383.0	O K	30 min Summer	18.790	0.490	0.0	5.4	5.4	439.7	O K	60 min Summer	18.859	0.559	0.0	5.4	5.4	502.3	O K	120 min Summer	18.934	0.634	0.0	5.4	5.4	569.2	O K	180 min Summer	18.978	0.678	0.0	5.4	5.4	608.6	O K	240 min Summer	19.008	0.708	0.0	5.4	5.4	635.2	Flood Risk	360 min Summer	19.044	0.744	0.0	5.4	5.4	668.2	Flood Risk	480 min Summer	19.065	0.765	0.0	5.4	5.4	686.4	Flood Risk	600 min Summer	19.075	0.775	0.0	5.4	5.4	696.1	Flood Risk	720 min Summer	19.080	0.780	0.0	5.4	5.4	700.1	Flood Risk	960 min Summer	19.113	0.813	0.0	5.4	5.4	730.1	Flood Risk	1440 min Summer	19.145	0.845	0.0	5.4	5.4	758.3	Flood Risk	2160 min Summer	19.165	0.865	0.0	5.4	5.4	776.7	Flood Risk	2880 min Summer	19.170	0.870	0.0	5.4	5.4	781.4	Flood Risk	4320 min Summer	19.055	0.755	0.0	5.4	5.4	678.1	Flood Risk	5760 min Summer	18.951	0.651	0.0	5.4	5.4	584.0	O K	7200 min Summer	18.843	0.543	0.0	5.4	5.4	487.8	O K	8640 min Summer	18.758	0.458	0.0	5.4	5.4	410.8	O K	10080 min Summer	18.686	0.386	0.0	5.4	5.4	346.6	O K	15 min Winter	18.778	0.478	0.0	5.4	5.4	429.3	O K	Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)	15 min Summer	224.312	0.0	351.6	19	30 min Summer	129.531	0.0	398.4	34	60 min Summer	74.799	0.0	502.0	64	120 min Summer	43.194	0.0	578.9	124	180 min Summer	31.327	0.0	628.2	184	240 min Summer	24.943	0.0	665.0	242	360 min Summer	18.090	0.0	718.4	362	480 min Summer	14.403	0.0	755.6	482	600 min Summer	12.070	0.0	781.4	602	720 min Summer	10.446	0.0	796.8	722	960 min Summer	8.644	0.0	800.4	960	1440 min Summer	6.620	0.0	764.7	1242	2160 min Summer	5.069	0.0	1244.5	1640	2880 min Summer	4.195	0.0	1365.8	2044	4320 min Summer	2.928	0.0	1385.8	2856	5760 min Summer	2.269	0.0	1499.1	3696	7200 min Summer	1.862	0.0	1537.1	4400	8640 min Summer	1.584	0.0	1567.6	5104	10080 min Summer	1.382	0.0	1590.9	5848	15 min Winter	224.312	0.0	388.8	19
Storm Event	Max Level (m)	Max Depth (m)	Max Infiltration (l/s)	Max Control (l/s)	Max Σ Outflow (l/s)	Max Volume (m³)	Status																																																																																																																																																																																																																																																																																	
15 min Summer	18.727	0.427	0.0	5.4	5.4	383.0	O K																																																																																																																																																																																																																																																																																	
30 min Summer	18.790	0.490	0.0	5.4	5.4	439.7	O K																																																																																																																																																																																																																																																																																	
60 min Summer	18.859	0.559	0.0	5.4	5.4	502.3	O K																																																																																																																																																																																																																																																																																	
120 min Summer	18.934	0.634	0.0	5.4	5.4	569.2	O K																																																																																																																																																																																																																																																																																	
180 min Summer	18.978	0.678	0.0	5.4	5.4	608.6	O K																																																																																																																																																																																																																																																																																	
240 min Summer	19.008	0.708	0.0	5.4	5.4	635.2	Flood Risk																																																																																																																																																																																																																																																																																	
360 min Summer	19.044	0.744	0.0	5.4	5.4	668.2	Flood Risk																																																																																																																																																																																																																																																																																	
480 min Summer	19.065	0.765	0.0	5.4	5.4	686.4	Flood Risk																																																																																																																																																																																																																																																																																	
600 min Summer	19.075	0.775	0.0	5.4	5.4	696.1	Flood Risk																																																																																																																																																																																																																																																																																	
720 min Summer	19.080	0.780	0.0	5.4	5.4	700.1	Flood Risk																																																																																																																																																																																																																																																																																	
960 min Summer	19.113	0.813	0.0	5.4	5.4	730.1	Flood Risk																																																																																																																																																																																																																																																																																	
1440 min Summer	19.145	0.845	0.0	5.4	5.4	758.3	Flood Risk																																																																																																																																																																																																																																																																																	
2160 min Summer	19.165	0.865	0.0	5.4	5.4	776.7	Flood Risk																																																																																																																																																																																																																																																																																	
2880 min Summer	19.170	0.870	0.0	5.4	5.4	781.4	Flood Risk																																																																																																																																																																																																																																																																																	
4320 min Summer	19.055	0.755	0.0	5.4	5.4	678.1	Flood Risk																																																																																																																																																																																																																																																																																	
5760 min Summer	18.951	0.651	0.0	5.4	5.4	584.0	O K																																																																																																																																																																																																																																																																																	
7200 min Summer	18.843	0.543	0.0	5.4	5.4	487.8	O K																																																																																																																																																																																																																																																																																	
8640 min Summer	18.758	0.458	0.0	5.4	5.4	410.8	O K																																																																																																																																																																																																																																																																																	
10080 min Summer	18.686	0.386	0.0	5.4	5.4	346.6	O K																																																																																																																																																																																																																																																																																	
15 min Winter	18.778	0.478	0.0	5.4	5.4	429.3	O K																																																																																																																																																																																																																																																																																	
Storm Event	Rain (mm/hr)	Flooded Volume (m³)	Discharge Volume (m³)	Time-Peak (mins)																																																																																																																																																																																																																																																																																				
15 min Summer	224.312	0.0	351.6	19																																																																																																																																																																																																																																																																																				
30 min Summer	129.531	0.0	398.4	34																																																																																																																																																																																																																																																																																				
60 min Summer	74.799	0.0	502.0	64																																																																																																																																																																																																																																																																																				
120 min Summer	43.194	0.0	578.9	124																																																																																																																																																																																																																																																																																				
180 min Summer	31.327	0.0	628.2	184																																																																																																																																																																																																																																																																																				
240 min Summer	24.943	0.0	665.0	242																																																																																																																																																																																																																																																																																				
360 min Summer	18.090	0.0	718.4	362																																																																																																																																																																																																																																																																																				
480 min Summer	14.403	0.0	755.6	482																																																																																																																																																																																																																																																																																				
600 min Summer	12.070	0.0	781.4	602																																																																																																																																																																																																																																																																																				
720 min Summer	10.446	0.0	796.8	722																																																																																																																																																																																																																																																																																				
960 min Summer	8.644	0.0	800.4	960																																																																																																																																																																																																																																																																																				
1440 min Summer	6.620	0.0	764.7	1242																																																																																																																																																																																																																																																																																				
2160 min Summer	5.069	0.0	1244.5	1640																																																																																																																																																																																																																																																																																				
2880 min Summer	4.195	0.0	1365.8	2044																																																																																																																																																																																																																																																																																				
4320 min Summer	2.928	0.0	1385.8	2856																																																																																																																																																																																																																																																																																				
5760 min Summer	2.269	0.0	1499.1	3696																																																																																																																																																																																																																																																																																				
7200 min Summer	1.862	0.0	1537.1	4400																																																																																																																																																																																																																																																																																				
8640 min Summer	1.584	0.0	1567.6	5104																																																																																																																																																																																																																																																																																				
10080 min Summer	1.382	0.0	1590.9	5848																																																																																																																																																																																																																																																																																				
15 min Winter	224.312	0.0	388.8	19																																																																																																																																																																																																																																																																																				
©1982-2020 Innovyze																																																																																																																																																																																																																																																																																								

RMA Environmental Ltd		Page 3
4 Swallow Court Devonshire Gate, Tiverton Devon, EX16 7EJ		
Date 29/09/2022 16:15 File C2432 GEOCELL.SRCX	Designed by rosie.tutton Checked by	
Innovyze Source Control 2020.1		

Rainfall Details


Rainfall Model	FEH
Return Period (years)	100
FEH Rainfall Version	1999
Site Location GB 630650 159550 TR 30650 59550	
C (1km)	-0.022
D1 (1km)	0.309
D2 (1km)	0.443
D3 (1km)	0.215
E (1km)	0.312
F (1km)	2.508
Summer Storms	Yes
Winter Storms	Yes
Cv (Summer)	0.750
Cv (Winter)	0.840
Shortest Storm (mins)	15
Longest Storm (mins)	10080
Climate Change %	+45

Time Area Diagram

Total Area (ha) 0.920

Time (mins)	Area
From:	To: (ha)
0	4 0.920

©1982-2020 Innovyze

RMA Environmental Ltd		Page 4
4 Swallow Court Devonshire Gate, Tiverton Devon, EX16 7EJ		
Date 29/09/2022 16:15 File C2432 GEOCELL.SRCX	Designed by rosie.tutton Checked by	
Innovyze Source Control 2020.1		

Model Details

Storage is Online Cover Level (m) 19.300

Cellular Storage Structure

Invert Level (m) 18.300 Safety Factor 2.0
Infiltration Coefficient Base (m/hr) 0.00000 Porosity 0.95
Infiltration Coefficient Side (m/hr) 0.00000

Depth (m)	Area (m²)	Inf. Area (m²)	Depth (m)	Area (m²)	Inf. Area (m²)
0.000	945.0	0.0	1.000	945.0	0.0

Hydro-Brake® Optimum Outflow Control

Unit Reference MD-SHE-0109-5400-1000-5400
Design Head (m) 1.000
Design Flow (l/s) 5.4
Flush-Flo™ Calculated
Objective Minimise upstream storage
Application Surface
Sump Available Yes
Diameter (mm) 109
Invert Level (m) 18.300
Minimum Outlet Pipe Diameter (mm) 150
Suggested Manhole Diameter (mm) 1200

Control Points	Head (m)	Flow (l/s)	Control Points	Head (m)	Flow (l/s)
Design Point (Calculated)	1.000	5.4	Kick-Flo®	0.643	4.4
Flush-Flo™	0.298	5.4	Mean Flow over Head Range	-	4.7

The hydrological calculations have been based on the Head/Discharge relationship for the Hydro-Brake® Optimum as specified. Should another type of control device other than a Hydro-Brake Optimum® be utilised then these storage routing calculations will be invalidated

Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)	Depth (m)	Flow (l/s)
0.100	3.8	1.200	5.9	3.000	9.0	7.000	13.5
0.200	5.2	1.400	6.3	3.500	9.7	7.500	13.9
0.300	5.4	1.600	6.7	4.000	10.3	8.000	14.4
0.400	5.3	1.800	7.1	4.500	10.9	8.500	14.8
0.500	5.1	2.000	7.5	5.000	11.5	9.000	15.2
0.600	4.7	2.200	7.8	5.500	12.0	9.500	15.6
0.800	4.9	2.400	8.1	6.000	12.5		
1.000	5.4	2.600	8.4	6.500	13.0		

©1982-2020 Innovyze

Appendix E: SuDS Maintenance Schedule

Table E1: Detention Basin/Balancing Pond Operation and Maintenance Requirements

Schedule	Required Action	Frequency
Regular maintenance	Litter, debris and trash removal.	Monthly.
	Grass cutting – for landscaped areas, spillways and access routes.	Monthly (during growing season), or as required.
	Grass cutting – meadow grass in and around basin.	Half yearly (spring before nesting season and Autumn).
	Manage other vegetation and remove nuisance plants.	Monthly (at start, then as required).
	Tidy all dead growth before start of growing season.	Annually.
	Remove sediment from inlets, outlets and forebay.	Annually (or as required).
	Manage wetland plants in outlet pool – where provided.	Annually.
Occasional maintenance	Re-seed areas of poor vegetation growth.	Annually, or as required.
	Prune and trim trees and remove cuttings.	2 years, or as required.
	Remove sediment from pre-treatment system when 50% full.	As required.
	Remove sediment from micropools if volume reduced by >25%.	3 – 10 years, or as required.
Remedial actions	Repair of erosion or other damage by re-seeding or re-turfing.	As required.
	Realignment of rip-rap.	As required.
	Repair/rehabilitation of inlets, outlets and overflows.	As required.
	Re-level uneven surfaces and reinstate design levels.	As required.
Monitoring	Inspect inlets, outlets and overflows for blockages and clear if required.	Monthly.
	Inspect banksides, structures, pipework etc for evidence of physical damage.	Monthly.
	Inspect inlets and pre-treatment systems for silt accumulation. Establish appropriate silt removal frequencies.	Half yearly.
	Check penstocks and other mechanical devices.	Half yearly.

Table E2: Geocellular Storage Operation and Maintenance Requirements

Schedule	Required Action	Frequency
Regular maintenance	Inspect and identify any areas that are not operating correctly. If required, take remedial action.	Monthly for 3 months, then annually
	Remove debris from the catchment surface (where it may cause risks to performance).	Monthly
	For systems where rainfall infiltrates into the tank from above, check surface of filter for blockage by sediment, algae or other matter; remove and replace surface infiltration medium as necessary.	Annually
	Remove sediment from pre-treatment structures and/or internal forebays.	Annually or as required
Remedial Actions	Repair/rehabilitate inlets, outlets, overflows and vents	As required
Monitoring	Inspect/check all inlets, outlets, vents and overflows to ensure that they are in good condition and operating as designed	Annually
	Survey inside of tank for sediment build-up and remove if necessary	Every 5 years or as required

Table E3: Permeable Paving Operation and Maintenance Requirements


Schedule	Required Action	Frequency
Regular maintenance	Brushing and vacuuming.	Three times per year or as required based on observations or manufacturers' recommendations.
Occasional maintenance	Stabilise and mow contributing and adjacent areas.	As required.
	Removal of weed.	As required.
Remedial actions	Remediate any landscaping which, through vegetation maintenance or soil slip, has been raised to within 50 mm of the level of the paving.	As required.
	Remedial work to any depressions, rutting and cracked or broken blocks considered detrimental to the structural performance or a hazard to users.	As required.
	Rehabilitation of surface and upper sub-structure	As required (if infiltration performance is reduced as a result of significant clogging).
Monitoring	Initial inspection	Monthly for three months after installation.

Schedule	Required Action	Frequency
	Inspect for evidence of poor operation and/or weed growth. If required take remedial action.	3-Monthly, 48 hours after large storms.
	Inspect silt accumulation rates and establish appropriate brushing frequencies.	Annually.
	Monitor inspection chambers	Annually.

Table E4: Bioretention (Rain Garden) Operation and Maintenance Requirements

Schedule	Required Action	Frequency
Regular inspections	Check operation of underdrains by inspection of flows after rain.	Annually
	Inspect infiltration surface for silting and ponding, record de-watering time of the facility and assess standing water levels in underdrain (if appropriate) to determine if maintenance is necessary.	Quarterly
	Assess plants for disease infection, poor growth, invasive species etc. and replace as necessary.	Quarterly
	Inspect inlets and outlets for blockage.	Quarterly
Regular maintenance	Remove litter and surface debris and weeds.	Quarterly (or more frequently for tidiness or aesthetic reasons)
	Replace any plants, to maintain plant density.	As required
	Remove sediment, litter and debris build-up from around inlets or from forebays.	Quarterly to biannually
Occasional maintenance	Infill any holes or scour in the filter medium, improve erosion protection if required.	As required
	Repair minor accumulations of silt by raking away surface mulch, scarifying surface of medium and replacing mulch.	As required
Remedial actions	Remove and replace filter medium and vegetation above.	As required but likely to be > 20 years

Appendix F: Southern Water Map



(c) Crown copyright and database rights 2022 Ordnance Survey 100031673
Data updated: 21/07/22

Scale: 1:1250
Map Centre: 629443,158319

Date: 17/08/22
Our Ref: 928590 - 2

Wastewater Plan A3
Powered by digdat

utility.reports@technicsgroup.com

GRS12523



The positions of pipes shown on this plan are believed to be correct, but Southern Water Services Ltd accept no responsibility in the event of inaccuracy. The actual positions should be determined on site. This plan is produced by Southern Water Services Ltd (c) Crown copyright and database rights 2022 Ordnance Survey 100031673. This map is to be used for the purposes of viewing the location of Southern Water plant only. Any other uses of the map data or further copies is not permitted.

WARNING: BAC pipes are constructed of Bonded Asbestos Cement.

WARNING: Unknown (UNK) materials may include Bonded Asbestos Cement.